



origin
DOORS AND WINDOWS

Origin Inline Slider

Operating Instructions

Opening the door

1. Insert the key into the lock, turn it 360° and remove.
2. Flip the handle up to disengage the locks.
3. Open the now unlocked door by sliding it across in the opening direction.
4. Depending on your configuration, to open the remaining doors, slide each door in same direction as you did with the lead door, until all doors are open or stage them where you want.

Closing the door

1. Start by pulling the lead door in the closing direction. From there, depending on your configuration, slide the remaining doors in the same direction, starting with the door closest to the lead door.
2. Once all doors are closed, engage the locks by flipping down the handle.
3. Once the locks are engaged, lock the doors by turning the key 360° anti-clockwise.

Helpful hints & tips:

Safety recommendations when handling and using the doors.

Danger of being caught

Pay attention to the possibility of being caught between the frame and the door while they're being operated.

Danger of falling

An open door poses a risk of people tripping or falling. Ensure you supervise children when the doors are open.

Maintenance Instructions

Your Origin Doors contain mechanical moving parts that will need to be lubricated periodically. This includes the locking mechanism and trolley wheels. Lubricate using silicone spray or grease and wipe away any excess with a non-abrasive cloth.

Routine Care of your Origin Doors

Powder coated aluminium profile and glass

Use a light, soapy solution (such as a diluted baby bath product) and non-abrasive cloth to wipe dirt from the doors and glass. Washing up liquid is not recommended, and do not use solvent based cleaning products. Please also refrain from using an abrasive cloth such as a scouring pad as the doors and glass can be scratched.

If you are in a marine environment, the doors and hardware should be washed down on a weekly basis with fresh water as it is common for harmful deposits to build up.

Before beginning any maintenance or construction work close to the doors and glass, it should be protected from dirt which can be originated from the site. Use plastics and weather-stripping as required.

Seals

Use a light, soapy solution and non-abrasive cloth to gently clean these. Do not use solvent based cleaning products on the seals.

Tracks

Use a small brush to loosen any debris from the track. Using a suitable vacuum cleaner with a thin attachment, vacuum up the debris in the track. Do not allow debris to build up in the track as this will affect the operation.



