

Configuration	Sizes Covered (up to)	Qualifying Hardware	Message Displayed on Confirmation	OSS Defaults	Additional Worksheet Information
Uneven + 0 (All thresholds)	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.
0 + Uneven (All thresholds)	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.
Even + 0 (All thresholds)	Sashes 1200mm x 2376mm	All (internal handle & cylinder only)	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
0 + Even (All thresholds)	Sashes 1200mm x 2376mm	All (internal handle & cylinder only)	To comply with SBD, a BSEN 356 P1A certified glass unit must be install into this product. To comply with SBD a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Uneven + Even (All thresholds)	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.
Even + Uneven (All thresholds)	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.
Uneven + Uneven (All thresholds)	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.
French Door (standard & non-weathered threshold only)	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.
Single Door (all thresholds)	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.
Single Door With Midrail	Sashes 1200mm x 2376mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit and/or an Origin decorative panel must be installed into this product.	Minimum glass weight increased to 25kg psqm. 3 star cylinder selected (full cylinders only)	SBD Certified serial plate required.

Configuration	Sizes Covered (up to)	Qualifying Hardware	Message Displayed on Confirmation	OSS Defaults	Additional Worksheet Information
Full Panel Single Door (all thresholds)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, an Origin decorative panel must be installed into this product.	Supply with an Origin panel	SBD Certified serial plate required.
Full Panel French Door (standard & Non-weathered threshold only)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, an Origin decorative panel must be installed into this product.	Supply with an Origin panel	SBD Certified serial plate required.
Full Glass Single Door (all thresholds)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Full Glass French Door (standard & Non-weathered threshold only)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Single Door With Midrail All Panels (all thresholds)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, an Origin decorative panel must be installed into this product.	Minimum glass weight increased to 25kg psqm. Supply with an Origin panel	SBD Certified serial plate required.
Single Door With Midrail All Glass (all thresholds)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Single Door With Midrail Glass and Panel (all thresholds)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass units and Origin decorative panels must be installed into this product.	Minimum glass weight increased to 25kg psqm. Supply with an Origin panel	SBD Certified serial plate required.
French Door With Midrail All Panels (standard & non-weathered threshold only)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, an Origin decorative panel must be installed into this product.	Supply with an Origin panel	SBD Certified serial plate required.
French Door With Midrail All Glass (standard & non-weathered threshold only)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
French Door With Midrail Glass & Panels (standard & non-weathered threshold only)	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass units and Origin decorative panels must be installed into this product.	Minimum glass weight increased to 25kg psqm. Supply with an Origin panel	SBD Certified serial plate required.
Single door coupled to an OW80 window	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass unit and/or an Origin decorative panel must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required on both products.
French door coupled to an OW80 window	Sashes 1200mm x 2376mm	All apart from letter plates	To comply with SBD, a BSEN 356 PIA certified glass unit and/or an Origin decorative panel must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required on both products.

Configuration	Sizes Covered (up to)	Qualifying Hardware	Message Displayed on Confirmation	OSS Defaults	Additional Worksheet Information
Side Hung	950mm x 1400mm	All	To comply with SBD a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Top Hung	1200mm x 1500mm	All	To comply with SBD a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Fixed	4.8sqm	N/A	To comply with SBD a BSEN 356 P1A certified glass unit must be installed into this product.	N/A	SBD Certified serial plate required.
Dummy	3.6sqm	All	To comply with SBD a BSEN 356 P1A certified glass unit must be installed into this product.	N/A	SBD Certified serial plate required.
Combinations (Including couplings)	All	All	To comply with SBD a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.

Configuration	Sizes Covered (up to)	Qualifying Hardware	Message Displayed on Confirmation	OSS Defaults	Additional Worksheet Information
Side Hung	865mm x 1750mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product..	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Top Hung	1470mm x 1462mm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
French Window	865mm x 1350	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Fixed	7sqm	N/A	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	N/A	SBD Certified serial plate required.
Dummy	3.6sqm	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	N/A	SBD Certified serial plate required.
Combinations (Including couplings)	All	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	Minimum glass weight increased to 25kg psqm.	SBD Certified serial plate required.
Gables	All	All	To comply with SBD, a BSEN 356 P1A certified glass unit must be installed into this product.	N/A	SBD Certified serial plate required.